









# A Distributed Online Heuristic for a Large-scale Workforce Task Assignment and Multi-Vehicle Routing Problem

Diego Deplano\*, Carla Seatzu\*, and Mauro Franceschelli\*

\*Department of Electrical and Electronic Engineering, University of Cagliari, Italy

IEEE 20th International Conference on Automation Science and Engineering (CASE), August 2024

#### Outline

- 1 Problem statement and contributions
- MILP formulation
- 3 Online gossip-based heuristic
- 4 Numerical simulation on real data
- **5** Conclusions and future work

#### Outline

•000

Problem statement and contributions

- Problem statement and contributions

## Problem of interest (the real case study of DEDEM S.p.A)

**Problem:** Managing a workforce of technicians responsible for refurbishing and repairing photo booths across the Italian territory.

Objective: Maximize the profit for the enterprise

#### Three-folded challenge:

- Task assignment
- Route planning
- Execution scheduling





Diego Deplano University of Cagliari, Italy

## Problem of interest (the real case study of DEDEM S.p.A)

# Main differences with the standard MVRP (multi-veichle routing problem):

- Each photo-boot (a task) generates an hourly profit (€/hour) once it has been refurbished/repaired:
  - Tasks may not be executed
- ② Each technician (a vehicle) has a daily cost (€/day):
  - Technicians may not be employed

#### Additional complexities:

- Time windows for technicians and tasks
- Skills required for the tasks' execution
- Multi-day assignment/routing/scheduling
- · Calendar of technicians' availability





Diego Deplano

#### Our main contributions are:

Problem statement and contributions

0000

- A MILP formulation of the complex optimization scenario of the DEDEM S.p.A. case study
- A gossip-based heuristic algorithm with the following features:
  - Scalability for large problem sizes
  - Real-time employment to deal with:
    - Delays on task execution and traveling times
    - New tasks available to be performed
    - Unexpected unavailability of the technicians
  - Geolocation privacy-preserving
- Numerical tests validating the approach by using real data drawn from DEDEM S.p.A.'s data

Diego Deplano University of Cagliari, Italy

- Problem statement and contribution:
- 2 MILP formulation
- Online gossip-based heuristic
- 4 Numerical simulation on real data
- Conclusions and future work

We consider an undirected graph G = (V, E) defined as follows:

- ullet The set of nodes V can be decomposed into three disjoint sets:
  - $S = \{1, ..., s\}$  is the set of technicians' depots and s is the total number of technicians;
  - $D = \bigcup_{\ell=1}^{d-1} D_\ell$  where  $D_\ell = \{\ell s + 1, \cdots, (\ell+1)s\}$  is the set of the technicians' depots corresponding to the  $\ell$ -th night and d is the total number of days;
  - $P = \{ds, \dots, ds + p\}$  is the set of tasks' position and p is the total number of tasks.
- The set of edges E representing the viable paths is such that:

$$E: \begin{cases} (i,j), \ (j,i) \in E & i,j \in P, \\ (i,j), \ (j,i) \in E & i \in S \cup D, j \in P, \\ ((\ell-1)s+i, \ell s+i) \in E & i \in S, \ \ell=1, \dots, d-1, \\ (i,j) \notin E & \text{otherwise,} \end{cases}$$

We adapt the multi-commodity flow formulation 1 to our case study and consider the variables:

- $X_{i,j} \in \{0,1\}$  denotes the motion of a technician through the  $(i,j) \in E$ .
- $U_{i,j} \in [0, \infty)$  denotes the initial time of motion from  $i \in V$  to  $j \in V$ .
- $F_{i,j,k} \in \{0,1\}$  denotes the motion of a technician from task k through  $(i,j) \in E$ .

$$f(X, F, U) = \text{FUEL}(X) + \text{TECH}(F) - \text{TASKS}(X, U).$$

with

$$\begin{aligned} \text{FUEL}(X) &= \sum_{(i,j) \in E} f_{ij} d_{ij} X_{i,j} \\ \text{TECH}(F) &= \sum_{i \in S} q_i \sum_{j \in P} F_{i,j,i} + \sum_{\ell \in I}^{d-1} \sum_{i \in D_\ell} q_{i-\ell s} \sum_{j \in P} F_{i,j,i} \\ \text{TASKS}(X,U) &= \sum_{j \in P} g_j \sum_{i \in V} \left[ (24 \cdot d - t_{ij} - \delta_j) X_{i,j} - U_{i,j} \right]. \end{aligned}$$

#### where

- $d_{ij}$  (km) denotes the distance of route (i, j);
- $f_{ij}$  ( $\leq$ /km) denotes the fuel cost of route (i,j);

000000

- $t_{i,i}$  (h) denotes the time needed to travel route (i, j);
- $\delta_i$  (h) denotes the expected amount of time needed to execution the task in position  $j \in P$ ;
- $q_i$  ( $\leq$ /h) denotes the profit of the photo booth associated to task  $i \in P$ :
- $q_i$  ( $\leq$ /day) denotes the cost of the technician for one day of work;
- d is the total number of days.

$$\min f(X, F, U) \tag{1}$$

s.t. 
$$\sum_{j \in V} X_{i,j} \le 1$$
,  $\forall i \in V$ , (each position is left at most once) (2)

$$\sum_{j \in V} (X_{i,j} - X_{j,i}) = 0, \quad \forall i \in V, \quad (each position is left if it is entered)$$
 (3)

$$\{(i,j) \in E \mid X_{i,j} = 1\}$$
 contains no circuit with zero depots
(subtour elimination constraints)
(4)

$$\{(i,j) \in E \mid X_{i,j} = 1\}$$
 contains no circuit with two or more depots (path elimination constraints) (5)

$$\{(i,j) \in E \mid U_{i,j} > 0\}$$
 all working days and time-windows are met   
(timing constraints) (6)

## Set of constraints: subtour/path elimintation

#### When a position $k \in P$ is visited, a commodity (think about a receipt) is collected

#### Subtour Elimination Constraints

Commodities can flow through edges in a tour  $(\forall i \in V, \ \forall i, k \in P \cup D, : i \neq i)$ :

$$0 \le F_{i,j,k} \le X_{i,j}.$$

Commodities must leave their position if in a tour  $(\forall k \in P \cup D)$ :

$$\sum_{j\in V} (F_{k,j,k} - X_{k,j}) = 0.$$

Commodities leave a position iff they visited it  $(\forall i, k \in P \cup D)$ :

$$\sum_{j \in P \cup D} F_{j,i,k} = \sum_{j \in V} F_{i,j,k}.$$

#### PATH ELIMINATION CONSTRAINTS

Commodities must return to a depot if in a tour  $(\forall k \in P \cup D)$ :

$$\sum_{j \in P \cup D} \sum_{i \in S} F_{j,i,k} \ge \sum_{j \in V} X_{j,k}.$$

Commodities first visited by a technician must return to their depots  $(\forall i \in S, \ \forall k \in P \cup D)$ :

$$\sum_{j \in P \cup D} F_{j,i,k} \ge X_{i,k}.$$

## Set of constraints: timing constraints

Technicians must leave/return their depots within the horizon time  $(\forall i \in S, \ \forall k \in P \cup D)$ :

$$T_i^s X_{i,k} \le U_{i,k} \le (T_i^e + 24(d-1))X_{i,k},$$
  

$$T_i^s X_{i,k} \le U_{k,i} \le (T_i^e + 24(d-1) - t_{k,i})X_{i,k}.$$

Technicians must leave/return their depots every night within the working time ( $\forall i \in V, \forall k \in D$ ):

$$(T_k^s - t_{i,k})X_{i,k} \le U_{i,k},$$
  
$$(T_k^e - t_{i,k} - \delta_k)X_{i,k} \ge U_{i,k}.$$

Technicians must not work on a free day  $\ell^{\star} \in \{1,\ldots,d\}$ :

$$X_{p,q} = 1$$
, where 
$$\begin{cases} p = (\ell^* - 1)s + i, \\ q = (\ell^* \% d)s + i, \end{cases}$$

where a % b returns the reminder after a/b.

Tasks must be executed within their time windows  $(\forall i \in V, \ \forall k \in P)$ :

$$(T_k^s - t_{i,k}) X_{i,k} + 24 \sum_{\ell \in D} F_{i,k,\ell} \le U_{i,k},$$
$$(T_k^e - t_{i,k} - \delta_k) X_{i,k} + 24 \sum_{\ell \in D} F_{i,k,\ell} \ge U_{i,k}.$$

Tasks must be executed after the previous task's position has been reached and the task has been executed  $(\forall kinP \cup D)$ :


$$\sum_{j \in V} U_{k,j} \ge \sum_{j \in V} \left( U_{j,k} + \left( t_{j,k} + \delta_k \right) X_{j,k} \right).$$

#### Outline

- Problem statement and contributions
- MILP formulation
- 3 Online gossip-based heuristic
- Mumerical simulation on real data
- 6 Conclusions and future work

#### ⇒ Gossiping:

- Nodes in a network are said to communicate through gossiping if, at any time, any node may communicate only to one random neighbor at a time;
- Gossiping is a way to spread information in a decentralized and asynchronous manner;
- ⇒ In our proposed heuristic optimization algorithm gossiping is used to solve local optimization problems between neighboring agents:
  - Each local optimization has a significantly smaller computational complexity with respect to the whole workforce problem;
  - The heuristic can be used both offline (to find a sub-optimal initial solution) and online (to deal
    with unexpected events and real-time changes in the problem);
  - In the online mode, the heuristic deals with:
    - Delays experienced by the technicians (e.g., traffic jams or difficulties in executing the tasks);
    - Sudden unavailability of agents (e.g., illness);
    - New tasks to be executed or new technicians available for executing tasks.







Fig. 1: Example of two graphs where the nodes represent the technicians depots: full graph (left) and Delaunay triangulation (right)


Diego Deplano University of Cagliari, Italy

```
Input: The sets of technicians S, days D, and tasks P: The initial Delaunay graph G_D = (S, E_D);
         The number m \in \mathbb{N} of unassigned tasks to be included in the local optimizations.
Initialize: Mark all edges as active E_A = E_D
 1: repeat indefinitely steps 2-21:
 2:
        while E_A = \emptyset do
            if technician i^* is late or changes task
 3:
                Mark edges of i^* as active: E_A = E_A \cup \{(i, j) \in E_D | i = i^* \text{ or } j = i^* \}
 4:
            end if
 5:
        end while
 6:
 7:
        Update technicians positions based on the tasks they are currently executing
        Save old edges E_D^- = E_D and reconstruct the Delaunav Graph \mathcal{G}_D = (S, E_D)
 8:
        Mark old edges as inactive E_A = E_A \cap E_D
 9:
        Mark new edges as active E_A = E_A \cup (E_D \setminus E_D^-)
10:
```

Diego Deplano


```
11:
        Pick an edge (i^*, j^*) at random from E_A and solve the local optimization problem where:
        (i) only technicians i^* and j^* are considered
        (ii) only tasks currently assigned to technicians i^* or j^* are considered, along with m \in \mathbb{N}
        randomly picked unassigned tasks in P
        (iii) the scheduling of the current and previous tasks must remain unchanged
        if the new solution improves the objective function
12:
            if agent i^* changes assignment
13:
                Mark its incident edges as active E_A = E_A \cup \{(i, j) \in E_D | i = i^* \text{ or } i = i^* \}
14:
            end if
15.
            if agent j^* changes assignment
16:
                Mark its incident edges as active E_A = E_A \cup \{(i, j) \in E_D | i = j^* \text{ or } i = j^* \}
17:
            end if
18.
            return the new assignment, schedule, and routing for technicians i^* and j^*
19:
        end if
20:
        Mark edge (i^*, j^*) as inactive E_A = E_A \setminus \{(i^*, j^*)\}
21:
```





Diego Deplano

## A simple example with 4 employees and 12 tasks (online)



Diego Deplano

- Problem statement and contribution:
- MILP formulation
- Online gossip-based heuristic
- 4 Numerical simulation on real data
- Conclusions and future work

- 932 tasks located in 5 italian regions (Lazio, Campania, Toscana, Umbria, Abruzzo)
- 16 technicians
- 5 days of work (one working week)

#### Parameters:

- Technicians start working at 7:00 AM  $(T_i^s=7)$  and finish working at 6:30 PM  $(T_i^e=18.5)$ , for all  $i \in S$ ;
- The cost of technicians for one day of work is  $\leq 50,00 \ (q_i = 50 \ \text{for all} \ i \in S)$ ;
- Tasks may be executed at any time ( $T^s = 7$  and  $T^e_i = 18.5$  for all  $p \in P$ );
- The duration of the tasks ranges from 1 minute to 5 hours  $(d_p \in [0.02, 5])$  for all  $p \in P$ , while the average duration is about 22 minutes;
- The profit of the tasks ranges from  $\leq 0.50$  to  $\leq 11.40$  per hour  $(g_p \in [0.5, 11.4]$  for all  $p \in P)$ , while the average profit is about  $\leq 1.80$ ;
- ullet The area containing all tasks is contained within a squared area of  $250~{
  m km}$  side length;
- Travel times have been computed by means of Google Maps APIs, while the fuel cost has been considered fixed for all roads and equal to about  $\leq 0.10$  per kilometer ( $f_{ij} = 0.10$  for any  $i, j \in V$ ).


tion Online gossip-based heuristic Numerical simulation on real data

### Offline solution



Real routes/scheduling provided by DEDEM

Task assigned: 814 Expected profit:  $\sim 281k \in$ 



Solution provided by our heuristic algorithm

Task assigned:  $832 (\sim 2\% \text{ more})$ 

Expected profit:  $\sim 326k \in (\sim 15\% \text{ more})$ 

Diego Deplano

#### Online solution

We consider the scenario in which the following unfortunate and unexpected event takes place:

One of the technician is not available at the beginning of the first day!

If not action is taken, then:

- 19 tasks won't be executed
- The expected profit loss amounts to  $\sim 11k \in$

#### Running our gossip-based heuristic one achieves results in:

- 17 out of the 19 tasks are re-assigned to other technicians in real-time
- The profit loss drops at  $\sim 1k \in (90\%)$  of the expected loss has been avoided)

#### Outline

- 6 Conclusions and future work

- A MILP formulation has been provided to solve a joint assignment/routing/scheduling problem inspired by the real case study of DEDEM S.p.A.:
- An heuristic gossip-based solution has been provided to solve the problem both offline and online to deal with dynamic changes in the problem formulation;

#### The future directions are:

- Include tasks with fixed profit and deadlines
- Derive a constant factor approximation
- Carry out Monte Carlo simulations with delays

Diego Deplano University of Cagliari, Italy











# A Distributed Online Heuristic for a Large-scale Workforce Task Assignment and Multi-Vehicle Routing Problem

Thank you for your attention!

Diego Deplano

**Email**: diego.deplano@unica.it **Webpage**: https://diegodeplano.github.io/

